

Calculation of the hydro-pneumatic suspension damper

S Britsin¹, M Ryabinin^{1,2} and E Sarach¹

¹Bauman Moscow State Technical University

²E-mail: ryabinin@bmstu.ru

Annotation. The paper considers general approaches to the design and calculation of the characteristics of hydropneumatic dampers that can be used in the suspensions of mobile cars. It is paid particular attention to the determination of the main hydraulic characteristics of the flow part of the damper, including a direct-acting belt valve, based on numerical simulation.

Introduction

The desire to increase the efficiency of transport equipment requires increasing its average speed.

As it is well known, a machine speed is limited and is determined by the movement conditions and the technical characteristics of the machine. Restrictions depending on driving conditions include restrictions on traction, on the uncontrolled movement danger and on the ride smoothness [1]. An increase in the specific power of modern machines and the correct choice of traction engines made it possible to remove a number of restrictions on the traction force [2]. The subject of work are the methods to reduce the likelihood of uncontrolled movement [3]. In this regard, the problem of improving the suspension systems of transport vehicles aimed at increasing the speed of movement on bumps is relevant.

An integral element of the suspension system of the transport vehicle is the damper. It serves to damp the vibrations of the sprung body when driving on rough roads.

The modern approaches to transport vehicles suspension theory require the selection of damping characteristics according to the criteria of smoothness using a simulation mathematical model of the movement of the vehicle along rough roads. The methods for determining the damping characteristics and mathematical models of the movement of transport vehicles for the study of ride smoothness are widely presented in the literature [4]–[14], therefore, in this work, the power characteristic of the damper is taken as the initial data. Particular attention in this work is paid to the design of throttle damper system valves, since their design feature allows to implement a given power characteristic.

The results obtained in this paper can be extended to the damping elements of both uncontrolled and controlled suspension systems, since the analysis of literature on controlled suspension systems [15]–[31] shows that it is advisable to use a passive suspension system with controlled damping for transport vehicles.

Initial data

The initial data for the engineering calculation of the damper will be considered a given power characteristic, suspension design and geometrical dimensions of the main surfaces, obtained on the basis of similar successful design solutions. Figure 1 shows the required power characteristic of the hydropneumatic spring damper, which must be ensured by calculating its main elements: throttles and valves. In this paper, we restrict ourselves to considering only the forward stroke of this diagram






Figure 1. Power characteristic of the damper (straight stroke)

The point A corresponds to the beginning of the bypass valve opening, and the point B to the valve output at the maximum opening and the maximum value of the valve gap area f (Fig. 2). The line 1 is provided with a constant throttling channel, which is available in the design, the line 3 is determined by the total conductivity of the fully open valve and constant throttling channel, and the form of curve 2 connecting the points Φ and B depends mainly on the increase degree in the flow rate through the valve from its opening. This dependence is largely determined by the spring deformation ratio when the valve h rises to its preliminary value and the emerging hydrodynamic force ratio to the spring force, i.e. on the pressure drop across the valve and the valve design features. The design of a direct acting hydraulic starting valve consists of a locking element with a diameter d_2 resting on a saddle with a diameter d_1 , having a sealing belt with a significant radial length "a", springs, and also a body with a supply channel with a pressure p_1 and discharge channel with a pressure p_2 . The force of the fluid pressure acting on the locking element of the valve is balanced only by the force of the spring. Due to the presence of an extended sealing belt, such a valve design is able to provide a shock-free fit on the saddle with a rapid increase in pressure p_2 in the internal space. The softness of the landing is achieved due to the intensive deceleration of the locking element when it approaches the surface of the saddle. The reason for this is the increase in pressure from the side of the fluid displaced from the radially extended sealing gap.

The soft fit and, consequently, the low wear of the sealing surfaces led to the widespread use and high reliability of such valves for systems where the number of their operating cycles is hundreds or thousands per minute. Flat starting valves allow the sealing element to move in the plane of contact with the saddle and therefore do not require an exact guide element. This explains the small size and simplicity of the design of such valves, they are used in hydropneumatic dampers. It is necessary to know the valve conductivity at its various openings for the suspension dynamic calculations of the machine, since the valve is an integral part of the flow channels of the damper.

There are methods for conducting dynamic calculations of the damper, taking into account the change in the conductivity of the valve from the Reynolds number [32]. It isn't always possible to use these data and it is necessary to observe the similarity between the flow part of the damper being developed and a sample with known characteristics. It is also a non-trivial task to take into account analytically the mutual influence of various hydraulic resistances forming the flow part of the damper.




Figure 2.Design diagram of a direct-acting starting valve

Methods

It is proposed to determine the resistance of the damper flow part in all the prescribed regimes using numerical simulation and to use the obtained values for further dynamic calculations of the suspension characteristics of the machine.




Figure 3. Mesh of the flow part of the damper with an opening height of 0.1 mm

For a numerical analysis of the flow part of the damper, it is used the CFD simulation software package ANSYS Fluent, which allows to simulate complex hydrodynamic processes in various devices. In order to obtain a series of results corresponding to different lift heights and flow rates for the valve, a parametric model was created with variable geometry and boundary conditions (the creation of so-called design points). Modeling the flow for different valve heights in narrow channels and slots requires a special approach for a computational grid with a number of cells from 4.2 to 5 million cells (Figure 3).




Figure 4. The field of distribution of static pressure at $h = 0,1\text{ mm}$ and $v = 0,2\text{ m/s}$




Figure 5. The field of velocity distribution at $h = 0,1\text{ mm}$ and $v = 0,2\text{ m/s}$

In order to describe the flow in the flow part, it is used the SST model of turbulence based on the turbulence kinetic energy transfer equation and the specific dissipation equation. This model describes well the near-wall layers of the flow and is able to describe flows at large pressure gradients


As boundary conditions was selected an inlet velocity of $v=0,1\text{ M/s}$ to $v=0,5\text{ M/s}$ and damper outlet pressure $p=0\text{ Pa}$

The simulation results are illustrated in Figures 4 and 5.

Conclusions

The comparison between the obtained values for flow coefficient of the flow part from the Reynolds number with the data given in the literature [32] shows their qualitative coincidence. The quantitative difference (Figure 6) is explained by the hydraulic resistance of the channels leading to the valve and the mutual influence of these resistances.

Also, the similarity of phenomena may be disrupted due to differences in the geometry of the flow part.



$\mu_1(Re_1)$ — Experimental data from the reference [32]

$\mu(Re)$ — Data obtained by numerical modeling

Figure 6. Comparison of flow coefficient values

References

- [1] Dmitriev A. A., Chobitok V. A., telminov A.V. Theory and calculation of nonlinear systems for springing tracked vehicles. - Moscow: Mashinostroenie, 1976. — 207 p.
- [2] Kotiev G O, Miroshnichenko A V, Stadukhin A A and Kositsyn B B 2019 Determination of mechanical characteristics of high-speed tracked vehicles traction motor with individual drive wheels (Journal of Physics: Conference Series) vol 1177(1)) p 012058
- [3] Ergin A A, Kolomejtseva M B and Kotiev G O 2004 Antiblocking control system of the brake drive of automobile wheel (PriboryiSistemyUpravleniya) vol 9 pp 11–13

- [4] Dyadchenko M. G., Kotiev G. O., sarach E. B. Construction and calculation of suspensions of high-speed tracked vehicles: Studies.stipend. - Moscow: MGTU publishing House. N. E. Bauman, 2007. - 40C.
- [5] Dyadchenko M. G., Kotiev G. O., Naumov V. N. Bases of calculation of systems of podressorivaniye of tracked cars on the computer: the Textbook. — M.: Publishing house of MGTU them. N. E. Bauman, 2002. - 52C.
- [6] Dhir A and Sankar S 1994 Analitical model for dynamics simulation of off-road Tracked Vehicles (Vehicle system dynamics) vol 24 pp 26–49
- [7] Dhir A and Sankar S 1997 Analitical wheel models for dynamic simulation of off-road tracked vehicles (Vehicle system dynamics) vol 27 pp 37–63
- [8] Duym S, Stiens R and Reybrouck K 1997 Evaluation of shock absorber models (Vehicle system dynamics) vol 27 pp 109–127
- [9] Lee K 1997 Numerical modeling for the hydraulic performance prediction of automotive monotube dampers (Vehicle system dynamics) vol 28 pp 25–39
- [10] Wong J Y 1997 Dynamics of Tracked Vehicles (Vehicle System Dynamics) vol 28 pp 197–219
- [11] Sarach E, Kotiev G and Beketov S 2018 *Methods for road microprofile statistical data transformation* (MATEC Web of Conferences) vol 224 p 04009
- [12] Klubnichkin V E, Klubnichkin E E, Kotiev G O, Beketov S A and Makarov V S 2018 *Interaction between elements of the track ground contacting area with the soil at curvilinear motion of the timber harvesting machine* (IOP Conference Series: Materials Science and Engineering) vol 386(1) p 012016
- [13] Weiss R A 1981 *Terrain Microroughness the Dynamic Response of Vehicles* (West Point (New York) ARO Report 82–1) 6 p
- [14] Shinozuka M 1971 *Simulation of a multivariate and multidimensional random processes* (Journal of the Acoustical Society of America) vol 49 № 1 pp 357–368
- [15] Venhovens P J Th 1991 *Semi-Active Suspension for Automotive Application*. (Delft: Univ. of technology) 28 p.
- [16] Venhovens P J Th 1994 *The Development and Implementation of Adaptive Semi-Active Suspension Control* (Vehicle System Dynamics) vol 23 pp 211–235
- [17] Karnopp D and Sang-Gyun So 1998 *Energy Flow in Active Attitude Control Suspensions: A Bond Graph Analysis* (Vehicle System Dynamics) vol 29 pp 69–81
- [18] Redfield R C 1991 *Performance of Low-bandwidth, Semi-Active Damping Concepts for Suspension Control* (Vehicle System Dynamics) vol 20 pp 245–267
- [19] Foag W A 1989 *Practical Control Concept for Passenger Car Active Suspension with Preview* (Proc. Instn. Mech. Engrs (London (UK))) p 203
- [20] Prem H A 1987 *Laser-based Highway-speed Road Profile Measuring System* (Proc. 10th IA VSD) p 37
- [21] Zhileykin M M, Kotiev G O and Nagatsev M V 2018 *Comparative analysis of the operation efficiency of the continuous and relay control systems of a multi-axle wheeled vehicle suspension* (IOP Conference Series: Materials Science and Engineering) vol 315(1), 012030
- [22] Zhileykin M M, Kotiev G O and Nagatsev M V 2018 *Synthesis of the adaptive continuous system for the multi-axle wheeled vehicle body oscillation damping* (IOP Conference Series: Materials Science and Engineering) vol 315(1), 012031
- [23] Crosby M J and Karnopp D C 1973 *The Active Damper - a New Concept for Shock and Vibration Control* (43rd Shock and Vibration Bulletin) vol H, June, pp 46–73.
- [24] Dhir A and Sankar S 1994 *Ride Dynamics of High-Speed Tracked Vehicles: Simulation with Field Validation* (Vehicle System Dynamics) vol 23 pp 379–409.
- [25] Gordaninejad F and Breese D 2000 *Heating of Magnetorheological Fluid Dampers* (Journal of Intelligent Materials, Systems and Structures, accepted, in press) vol 4 pp 45–56.
- [26] Han-Shue Tan and Bradshaw T 1998 *Validation of the Harshness Problem of Automotive Active Suspensions* (Vehicle System Dynamics) vol 30 pp 89–115.

- [27] Hrovat D, Margolis D and Hubbard M 1988 *An Approach Toward the Optimal Semi-Active Suspension* (Journal Dynamics System. Measurement and Control) vol 110 № 3 pp 288–296.
- [28] Wang X and Gordaninejad F 2000 *Flow Analysis of Field-Controllable, Electro- and Magnetno-Rheological Fluids Using Herchel-Bulkley Model* (Journal of Intelligent Materials, Systems and Structures, accepted, in press) vol 2 pp 87–121.
- [29] Yokoyama M, Hedrick J and Toyama S 2001 *A Model Following Sliding Mode Controller for Semi-Active Suspension Systems with MR Dampers* (Proceedings of the American Control Conference, Arlington, VA June 25-27) P. 53–58.
- [30] Yu F and Crolla D 1998 *An Optimal Self-Tuning Controller for an Active Suspension* (Vehicle System Dynamics) vol 29 pp 51–65.
- [31] Yu F and Crolla D 1998 *State Observer Design for an Adaptive Vehicle Suspension* (Vehicle System Dynamics) vol 30 pp 457–471.
- [32] Kirillovsky Yu. L. Hydraulic valves. Study guide for the course and diploma projects. M: MSTU publishing House. N. E. Bauman, 1977. -64 p.: Il.